

Portable Printer

Model: SP-T9



Features:

- *Mobile thermal receipt printer
- *Portable POS terminal
- *Direct thermal printing method
- *Quick and efficient printing
- *Rugged design withstands drop up to 1.2m
- *Long lasting lithium-ion battery (7.4V/2,100mAh)
- *Easy drop-in clamshell paper loading
- *Supports wide variety of serial and wireless communication options
- *Continuous printing even battery is charging
- *Easy to store setup parameters by setup tools

Applications:

- *Mobile Sales
- *Mobile Finance Service
- *Mobile Police Work Solution
- *Lottery

Specifications:

Print	Printing Method	Thermal Line
	Printing Speed	80mm/s(average)
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	IBM character set II, GB2312-80 (Chinese)
	Print Font	ANK: 12 x24 Chinese: 24 x 24
	Character per Line	48
Paper Spec	Paper Type	Thermal paper/label paper
	Paper Width	80±0.5mm or 76±0.5mm
	Paper Roll Diameter	Max: 60.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 to 0.07mm
Paper Supply Method		Drop-in Easy loading
Reliability	MCBF	15 million lines
	TPH	100km
Barcodes		EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128
Emulation		ESC/POS
Sensor		Paper End Sensor
Interface		T9-BT: USB, Bluetooth ; T9U: USB
Power Adaptor		DC12V/2A
Battery Power		DC7.4V, 2.1A rechargeable Li-ion battery
Battery duration		100m continuous printing
Physical	Weight	260g(excluding roll paper)
	Dimension (WxLxH)	103X99X46mm
	Color	Beige/Black